


FM HYDRAULIC OIL Series

Product Information

Hydraulic fluids for food and beverage processing equipment



FM HYDRAULIC OIL 15, 32, 46, 68 and 100 are anti-wear multi-purpose lubricants, which are specially designed for use in the food and beverage processing and packaging industry.

They are based on a careful blend of base fluids and selected additives chosen for their ability to meet the stringent requirements of the food and beverage industry.

Registered by NSF (Class H1) for use where there is potential for incidental food contact. Produced according to FLT Quality Standards, in facilities where HACCP audit and Good Manufacturing Practice have been implemented and form part of the quality and hygiene management systems ISO 9001 and ISO 21469.

CERTIFICATIONS AND SPECIFICATIONS

- NSF H1
- Kosher
- Halal
- DIN 51524 HLP
- ISO 6743-4 L-HM



PERFORMANCE FEATURES

- The base fluid has been selected for its ability to provide good lubrication under variety of applications
- Good anti-wear and extreme pressure characteristics
- Good anti-oxidant properties
- Good air release and antifoam characteristics
- Good water separation characteristics
- Neutral odor and taste

SEAL AND PAINT COMPATIBILITY

Compatible with the elastomers, gaskets, seals and paints normally used in food machinery lubrication systems.

HANDLING AND STORAGE

All food grade lubricants should be stored separately from other lubricants, chemical substances and foodstuffs and out of direct sunlight or other heat sources. Store between 32°F and +100°F. Provided that the product has been stored under these conditions we recommend to use the product within 5 years from the date of manufacture. Upon opening a pack, the product must be used within 2 years (or within 5 years of date of manufacture, whichever is the sooner).

APPLICATIONS

- Hydraulic systems
- Hydrostatic gears
- Plain and anti-friction bearings
- General purpose lubrication including light duty gearboxes
- Circulating oil systems

TYPICAL CHARACTERISTICS (Typical for current production. Variations in these characteristics may occur.)

			FM HYDRAULIC OIL				
			15	32	46	68	100
Property		Test Method					
NSF Reg. No.			133338	133345	133347	133350	133351
Colour			Colorless				
Density at +15 °C	kg/m ³	ASTM D 4052	852	859	866	869	872
Flash Point	°C	ASTM D 92	400	425	425	425	425
Pourpoint (°C)	°F	ASTM D 97	-10 (-23)	-6 (-21)	0 (-18)	0 (-18)	0 (-18)
Kin. Visc.(base oil) at +40°C	mm ² /s	ASTM D 445	15	32	46	68	100
Kin. Visc. (base oil) at +100°C	mm ² /s	ASTM D 445	3.3	6	7.1	9	11.6
Viscosity Index		ASTM D 2270	95	105	105	105	100
Water Separability		ASTM D 1401		40-40-0 (10)	40-10-0 (10)	40-40-0 (10)	40-40-0 (10)



FUCHS LUBRITECH
 A division of Fuchs Lubricants Co.
 17050 Lathrop Ave.
 Harvey, IL 60426
 Tel. 708-333-8900
 email: cassida.lubricants@fuchs.com
www.fuchs.com

As far as we know these information reflect the current state of knowledge and our research. They cannot, however, be taken as an assurance about the properties nor as a guarantee of the suitability of the product for the individual case in point. Before using our products the purchaser must, therefore, check the suitability and be satisfied that the output will be satisfactory. Our products are continually being up-dated. We reserve the right, therefore, to alter the information of this product information at any time and without prior announcement. We are specialized in developing products for extreme tribological problems in cooperation with end users. FUCHS LUBRITECH provides service and individual advice. Please contact us! E-Mail: cassida.lubricants@fuchs.com