



ISO-9001 Registered Quality System.  
ISO-21469 Compliant.

#### Sales, Service & Distribution Center

Newark, NJ 07105  
Phone: 973-589-9150 Fax: 973-589-4432

#### Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605  
Phone: 419-691-2491 Fax: 419-693-3806

#### Sales and Tech Service Support

Phone: 1-800-733-4755

### LUBRIPLATE SUPER FML LUBRICANTS

\*NSF H-1 Registered

"These products are certified OU Kosher Pareve"

"These products are Halal certified"

LUBRIPLATE Super FML Lubricants are among the most popular in the food industry as indicated by recent industry surveys. LUBRIPLATE FML Lubricants are white in color and due to their unexcelled lubrication characteristics, offer the utmost in lubrication and cleanliness. LUBRIPLATE FML greases provide exceptional anti-wear properties.

Typical tests on LUBRIPLATE Super FML Lubricants are as follows:

<u>LUBRIPLATE PRODUCT</u>	<u>SOAP</u>	<u>N.L.G.I. DENSITY NUMBER</u>	<u>PENETRATION (WORKED @ 77°F)</u>	<u>DROPPING POINT</u>	<u>MINERAL OIL VISCOSITY</u>
Super FML-0	Anhydrous Calcium	0	355/385	280°F/138°C	750 SUS @ 100°F 144 cSt @ 40°C
Super FML-1	Anhydrous Calcium	1	310/340	285°F/141°C	750 SUS @ 100°F 144 cSt @ 40°C
Super FML-2	Anhydrous Calcium	2	265/295	285°F/141°C	750 SUS @ 100°F 144 cSt @ 40°C

LUBRIPLATE Super FML Lubricants are available in the following packages:

<u>Packaging Available</u>	<u>FML-0</u>	<u>FML-1</u>	<u>FML-2</u>
Case, 24/14 oz. Cans	L0143-001	L0144-001	L0145-001
Case, 6/6 lb. Cans	L0143-006	-----	L0145-006
35 lb. Pail	L0143-035	L0144-035	L0145-035
120 lb. Drum	L0143-039	L0144-039	L0145-039
410 lb. Drum	L0143-040	L0144-040	L0145-040
Case, 12/11 oz. Aerosol Cans	-----	-----	L0145-063
Case, 40/14½ oz. Grease Gun Cartridges	-----	-----	L0145-098
Bulk Bins	(Contact your LUBRIPLATE District Manager)		

"The LUBRIPLATE FML Series contain no components derived from TSE/BSE relevant animal species, therefore, it is compliant with the requirements of the TSE Note for Guidance EMEA/410/01 Rev. 2, October 2003".

\*NSF H-1 Registration No's  
(Meets USDA 1998 Guidelines)

125742

125740

125741

126087 (Aerosol)

\*Authorized by NSF for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

\*NSF – National Sanitation Foundation

Manufactured with ingredients that comply with FDA 21 CFR 178.3570.