



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105
Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605
Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE FP-150 & LUBRIPLATE FP-150-L

*NSF H-1 Registered

“These products are certified OU Kosher Pareve”

“These products are Halal certified”

LUBRIPLATE FP-150 and LUBRIPLATE FP-150-L are tacky; waterproof adhesive oils, which will resist heavy water wash down and steam. They are NSF H-1 Registered oils for use in helical gear boxes, chains, linkages, cams, slides and wherever a drip-less adhesive fluid lubricant is desired.

<u>Typical Tests</u>	<u>FP-150</u>	<u>FP-150-L</u>
Viscosity SUS 100°F	1950	510
cSt 40°C	367	103
Viscosity SUS 210°F	126	67
cSt 100°C	25	12
Viscosity Index	93	108
API Gravity	28.4	30.2
Flash Point	395°F/202°C	410°F/210°C
Fire Point	455°F/235°C	450°F/232°C
Pour Point	0°F/-18°C	-5°F/-21°C

LUBRIPLATE FP-150 and LUBRIPLATE FP-150-L are available in the following:

<u>Packaging Available</u>	<u>Part Numbers</u>	
	<u>FP-150</u>	<u>FP-150-L</u>
4/1 gallon plastic jugs	L0735-057	L0736-057
5 gallon pail	L0735-060	L0736-060
16 gallon drum	L0735-061	L0736-061
55 gallon drum	L0735-062	L0736-062
<u>*NSF H-1 Registration No's</u> (Meets USDA 1998 Guidelines)	<u>126123</u>	<u>126124</u>

*Authorized by NSF for use in food processing facilities as a lubricant or anti-rust agent on equipment in which there may be incidental contact involving the lubricated part and the edible product.

*NSF – National Sanitation Foundation

Manufactured with ingredients that comply with FDA 21 CFR 178.3570.

Printed in USA
Revised 4/16/08