



ISO-9001 Registered Quality System.
ISO-21469 Compliant.

Sales, Service & Distribution Center

Newark, NJ 07105

Phone: 973-589-9150 Fax: 973-589-4432

Manufacturing, Sales, Service & Distribution Center

Toledo, OH 43605

Phone: 419-691-2491 Fax: 419-693-3806

Sales and Tech Service Support

Phone: 1-800-733-4755

LUBRIPLATE Poly HP-2

*NSF H2 Registered

LUBRIPLATE Poly HP-2 is a polyurea-thickened lubricating grease formulated with the highest quality paraffinic base oils available. Fortified with corrosion and oxidation inhibitors, LUBRIPLATE Poly HP-2 is an excellent choice for the lubrication and protection of high-speed electric motor bearings as well as other industrial applications.

Typical Properties

NLGI Grade		2
Penetration -		
Unworked		265
Worked, 60 Strokes		280
Thickener		Polyurea
Texture		Smooth & Buttery
Appearance		Red
Mineral Oil Viscosity -		
SUS @ 100°F		650
cSt @ 40°C		128
Viscosity Index		90 Min.
Oxidation Stability, PSI Drop	(ASTM D942)	5 Max.
Dropping Point	(ASTM D2265)	500°F
Copper Corrosion	(ASTM D130A)	1b
Oil Separation	(ASTM D1742)	< 3.0%
Four Ball Weld	(ASTM D2596)	340 kg.
Corrosion Resistance	(ASTM D1743)	Pass

Packaging Available

35 lb. Pail
120 lb. Quarter Size Drum
Carton, 40/14.5 oz. Cartridges

Part No.

L0191-035
L0191-039
L0191-098

*NSF H2 Registration No. 132279. (This product is acceptable as a lubricant where there is no possibility of food contact (H2) in and around food processing areas. Such compounds may be used as lubricants, release agents, or antirust films on equipment and machine parts in locations in which there is no possibility of the lubricant or lubricated part contacting edible products.