



**PETRON
PLUS™
FORMULA 7**



**PETRON
PLUS™
FORMULA 7
HI-TEMP, EXTREME-PRESSURE MULTI-
PURPOSE LITHIUM COMPLEX GREASE**

▶ **PART NO.'S: 00880, 00881, 52163, 52164**

TECHNICAL DATA SHEET

Petron Plus™ Formula 7 High- Temp Multi-Purpose Extreme Pressure Lithium Complex Grease is the latest in lithium complex grease technology for Industrial applications. It can be applied with complete confidence in automotive and industrial plain and anti-friction bearings, in hot or cold environments, under wet or dry conditions, and with light or heavy loads.

Because of its wide range of application possibilities, coupled with an special extreme pressure additives system, Petron Plus Formula 7 High- Temp Multi-Purpose E.P. Lithium Complex Grease is truly a grease for all seasons. Contains no heavy metals or chlorine compounds. Also friendly to copper containing components at high temperature.

This is a excellent shear stable product with exceptional extreme pressure characteristics and excellent water resistance, it is recommended for on and off-road equipment, fleet and commercial applications. It has excellent mobility characteristics at low temperatures.

Another outstanding feature is its compatibility with a wide variety of seal materials, such as Nitrile, Silicone, Hytrel, Viton and Neoprene.

Available in 14 ounce tubes, 35 lbs pails, 120 lb keg, & 400 lbs drums.

APPLICATIONS:

1. Automotive & Industrial applications
2. Plain and anti-friction bearings.
3. On & Off-road Equipment.
4. Fleet & commercial applications.
5. USDA H-2 Food Grade applications.

FEATURES:

1. Excellent grease.
2. Long life at higher temperatures.
3. Excellent higher extreme pressure characteristics.
4. Excellent rust protection.
5. Excellent low temperature properties.
6. Excellent shear stability characteristics.
7. Excellent water resistance.
8. Contains no heavy metals or chlorine.
9. USDA H-2 Food Grade.

BENEFITS:

1. Contains no heavy metals or chlorine.
2. Long Life.
3. Reduced maintenance costs.
4. Excellent mobility characteristics at low temperatures.

PETRON PLUS™ GLOBAL, INC.

P.O. BOX 1906 HUTCHINSON, KS 67504 USA, 620/663-1800 Phone, 620/663-8560 Fax,
www.petronplus7.com

www.petronomics.com

TYPICAL SPECIFICATIONS:

PETRON PLUS™

FORMULA 7

HI-TEMP, EXTREME-PRESSURE, MULTI-PURPOSE LITHIUM COMPLEX GREASE

Part No.,	00880, 00881, 52163, & 52134
NLGI, Consistency Grade, ASTM D-217, .	2
Thickener,	Lithium Complex
Texture,	Smooth/Tacky
Dropping Point, deg F, Min, ASTM D-2265,	550
Worked Penetration, ASTM D-217,	265 - 295
Change after 100,000 Strokes, ASTM D-217,	+20
Copper Corrosion, ASTM D-4043, Rating,	1a
Rust Prevention, ASTM D-1743, .	Pass
Timken OK Load, 10 minutes, lbs., ASTM D-2509,	80
Four Ball E.P. Test, Weld Point, Kg, ASTM D-2596,	500
Four Ball Wear Scar Dia. Mm, ASTM D-2266,	50
Water Washout, 20% water/175°F, % Loss, ASTM D 1264 modified,	2.0
Water Spray Off, % wt, Max, ASTM D-4049,	10
Wheel Bearing Leakage, gms, ASTM D-1263,	3.0
Color, .	Red

BASE OIL CHARACTERISTICS:

***Viscosity without Polymer**

* @ 40 deg. C, cSt.,	>450
* @ 100 deg. C, cSt.,	28.4
* @ 100°F, SUS.,	2429
* @ 210°F, SUS.,	140

Distributed By:

December., 2010

Warranty: All products purchased from Petron Plus Global, Inc., (PPGI) are subject to terms and conditions set out in the contract, order acknowledgment and/or bill of lading. PPGI warrants only that its product will meet those specifications designated as such herein or in other publications. All other information supplied by PPGI is considered accurate but is furnished upon the express condition that the customer shall make its own assessment to determine the product's suitability for a particular purpose. No warranty is expressed or implied regarding such other information, the data upon which the same is based, or the results to be obtained from the use thereof; that any product shall be merchantable or fit for any particular purpose, or that the use of such other information or product will not infringe any patent.