

CORROSION CONTROL GREASE NO. 2

DESCRIPTION:

TruBlend Tru*grease* **CC** Corrosion Control Grease is an extreme pressure/antiwear general purpose grease with superior anti-corrosion properties. This product has exceptional mechanical stability, water resistance and high temperature performance. It contains no harmful metals or other environmentally undesirable components, and is suitable for use wherever a heavy duty, high temperature corrosion control grease is required.

FEATURES:

- Heavy duty Extreme Pressure and antiwear performance.
- Excellent resistance to oxidation and corrosion.
- High dropping point (572°F, 300°C).
- Excellent mechanical stability.
- Enhanced water resistance.
- Phenol, chromium, and PCB-free per EPA 420.1, 3020A/7191, 8081.

TECHNICAL DATA:

Trugrease		CC^2		
NLGI Grade:	ASTM D217	2		
Color:	Visual	Tan		
Dropping Point, °F (°C):	ASTM D566	572 (300)		
Worked Penetration, 60	ASTM D217	270		
Timken OK Load, lbs:	ASTM D2509	65		
4-Ball EP	ASTM D2596			
LWI, kgf:		65		
Weld Point, kg:		500		
4-Ball Wear, mm:	ASTM D2266	.39		
Wheel Bearing Leakage, gm:	ASTM D1263m	.4		
Bearing Life Performance, hrs:	ASTM D3527	180		
Rust Test Rating:	ASTM D1743	1, 1, 1		
Salt Fog Corrosion, hrs:	ASTM B117	4000		

AVAILABLE PACKAGING:

14oz. Tubes in 10 Pack or 50 Tube Case, 35lb. Pails, 120lb. Kegs, 400lb. Drums.



MOTOR OIL, INC 1500 Jarvis Avenue Elk Grove Village, IL 60007

PHONE: 847-956-7550 www.motoroilinc.com