

Trugrease PU²

POLYUREA LUBRICATING GREASE NO. 2

DESCRIPTION:

TruBlend Trugrease PU is a polyurea based, extreme pressure grease with antiwear and anticorrosion additives. This product has exceptional mechanical stability and high temperature performance. Its dielectric properties make it an excellent choice for lubricating electric motor bearings and shafts. It contains no harmful metals or other environmentally undesirable components, and is suitable for use wherever a heavy duty general purpose polyurea grease is required.

FEATURES:

- ◆ Heavy duty Extreme Pressure and antiwear performance.
- ◆ Excellent resistance to oxidation and corrosion.
- ◆ High dropping point (500°F, 260°C).
- ◆ Excellent mechanical stability.
- ◆ Electric motor protection.
- ◆ Phenol, chromium, and PCB-free per EPA 420.1, 3020A/7191, 8081.

TECHNICAL DATA:

	Trugrease	PU ²				
NLGI Grade:	ASTM D217	2				
Color:	Visual	Blue				
Worked Penetration, 60	ASTM D217	265-295				
Dropping Point, °F (°C)	ASTM D566	500 (260)				
Timken OK Load, lbs:	ASTM D2509	60				
4-Ball EP	ASTM D2596					
LWI, kgf:		50				
Weld Load, kg:		400				
Rust Test Rating:	ASTM D1743	Pass				
Copper Corrosion:	ASTM D4048	1B				
Oxidation, PSI Drop, max:	ASTM D942	5				
Water Washout, % Loss, max:	ASTM D1264	10				
Oil Separation, % Loss, max:	ASTM D1742	5				

AVAILABLE PACKAGING:

14oz. Tubes in 10 Pack or 50 Tube Case, 35lb. Pails, 120lb. Kegs, 400lb. Drums.



MOTOR OIL, INC
2250 Arthur Avenue
Elk Grove Village, IL 60007
PHONE: 847-956-7550 www.motoroilinc.com